## <u>14' 2460 Brutus Eagle Pro Service Body</u> on an 122" CA chassis

Brutus Eagle Pro Features: Body length -171'' + 22'' workbench bumper Body width – 99" Cabinet height – 60" Cabinet depth -24" Cabinet drop – 6" Cabinets – Single wall 11 gauge A80 galvaneal steel Cabinet tops – Double wall 11 gauge A80 galvaneal steel Cargo bay walls – Double wall 11 gauge A80 galvaneal steel Wheel wells – Single wall 11 gauge A80 galvaneal steel Main sills – 2" x 3" steel structural tubing Cross sills – 2" x 4" x 10 gauge steel channels on 12" centers <u>Flooring</u> – Double wall 11 gauge A80 galvaneal steel Doors – Single wall 11 gauge A80 galvaneal steel Shelving – Galvaneal steel with infinitely adjustable track system Hinges – Painted stainless steel Handles – Polished stainless steel Latching – 3-point stainless steel Door retainers - Stainless steel door springs Cabinet pressurization – Dual fan motors with rooftop filters and covers for over pressurizing body to keep out dust, snow, and moisture Door seals - Rubber bulb seals Wiring – Watertight electrical relay box with master switches, Weatherpak connectors, and continuous protective loom Interior lights – Recessed rope lighting for full illumination with no shadows Exterior floodlights – Bosch 8" halogens with individual switches on lights and master switch, lights can be rotated 360 degrees and tilted 180 degrees Running Lights – Rubber mounted LED's Paint protection – Stainless steel bonded to the cabinet fronts and rears -Stainless steel bonded below each door opening -Body and frame is fully undercoated Paint – White PPG Delfleet polyurethane

## Brutus Body Specifications

Driver side #1 – 60"H x 54"W x 24"D

2-Vertical aluminum doors

1-Master switch panel

1-Cabinet pressurization system

1-7 drawer tool cabinet with top shelf (30" wide)

1-7 drawer tool cabinet with top shelf (18" wide)

1-Bookshelf

1-Rope lighting

Driver side #2 – 60"H x 36"W x 24"D

2-Vertical doors3-Shelves1-Rope lighting

## Driver side #3 – 35"H x 51"W x 24"D

2-Vertical doors1-Shelf1-Rope lighting

#### Driver side #4 – 60"H x 30"W x 24"D

1-Vertical door
1-Crane reinforcement
1-Shelf
1-Reelcraft <sup>1</sup>/<sub>2</sub>" x 50' spring rewind air reel with rear body access through sealed box
1-Air regulator, filter, and luber system
1-Hook for crane controller and cable (front wall)
1-Rope lighting

#### <u>Passenger side #1 – 60"H x 20"W x 24"D</u>

1-Vertical door
 2-Bottle holders with wear pads (front wall)
 2-Gear hooks (2 rear wall)
 1-Aluminum oilfield vent package

## Passenger side #2 – 60"H x 38"W x 24"D

2-Vertical doors1-Master switch panel1-Cabinet pressurization system3-Shelves1-Rope lighting

#### Passenger side #3 – 60"H x 32"W x 24"D

2-Vertical doors3-Shelves1-Rope lighting

## Passenger side #4 – 35"H x 51"W x 24"D

2-Vertical doors2-Shelves1-Rope lighting

## Passenger side #5 – 60"H x 30"W x 24"D

1-Vertical door3-Shelves1-Rope lighting

## Cargo bay - 171"D x 51"W x 43"H (8" raised roof)

- 1-Sliding aluminum roof system with peaked profile for shedding water and snow, Teflon side sliders, double rear doors with stainless latching. Roof can slide forward from the rear or slide back from the front
- 6-Flush mount d-ring tie downs (5,000 lb capacity each)

## Workbench bumper – 99"W x 22"D

- 1-15"H x 18"W x 99"D interior cabinet with side doors and stainless hardware and trim
- 1-3/8" smooth steel top plate with rounded corners, clamping lip, and grip tape
- 1-Vice mounting plate (passenger side)
- 1-Steel diamond plate bumper
- 1-2" receiver hitch with 7 blade plastic plug
- 1-Pintle hitch provision
- 1-Back-up alarm
- 1-7" steel diamond plate bumper

# Misc. features

- 2-Rear mud flaps
- 2-Aluminum grab handles with rubber grips
- 4-Bosch 8" rooftop swivel halogen floodlights

1-Spring mounted body sub frame to permit chassis flex on severe off road applications