## <u>11' Brutus BL6048S Steel Service Body</u> For an 84" CA light duty chassis

## Brutus Body Features

<u>Body length</u> $- 132'' + 7''$ step bumper
$\overline{\text{Body width}} - 96$ "
<u>Cabinet height – 60" and 48"</u>
Cabinet depth – 24"
Cabinet drop – None
<u>Cabinets</u> – 12 gauge all welded steel
<u>Cargo bay walls</u> $- 12$ gauge all welded steel
<u>Wheel wells</u> – 10 gauge all welded steel
Main sills – 3" x 4" steel heavy-wall tubing
<u>Cross sills</u> $-3$ " x <sup>1</sup> /4" steel channel
Flooring $- 1/8$ " smooth steel
$\underline{\text{Doors}} - 12$ gauge steel
<u>Shelving</u> $- 1/8$ " aluminum that are adjustable in 2" increments
Hinges – Polished stainless steel
Handles – Polished stainless steel
Latching – 3-point stainless steel
<u>Door retainers</u> – Stainless steel door springs that lock into position
<u>Cabinet venting</u> – Bottom venturi's with drain holes to remove moisture build-up
<u>Door seals</u> – Rubber bulb seals that are glued into a u-shaped moulding
Drip mouldings – Glue bonded aluminum gutters that channel water away from the doors
Wiring – Watertight electrical relay box with master switches, Weatherpak connectors,
and continuous protective loom
Interior ceiling lights – Individual switches on lights with master switch
Interior door lights - Individual switches on lights with master switch, lights can be
swivelled 180 degrees
Exterior floodlights – Bosch 8" halogens with individual switches on lights and master
switch, lights can be rotated 360 degrees and tilted 180 degrees
<u>Running Lights</u> – Rubber mounted LED's
<u>Warranty</u> – 3-year structural, 3-year limited paint, and 5-year paint fade
Paint protection – 3M vinyl coatings on cabinet front, bottom, and wheel well edges
-3M rubberized wheel well coating
-Hippo Liner coated bumper and cargo bay floor
-Aluminum diamond plate bonded to the cabinet fronts
Body finish – Fully body worked for a smooth exterior with no seams or weld joints
Paint – White PPG Delfleet polyurethane
Dentus Dody Specifications

## Brutus Body Specifications

Driver side #1 – 60"H x 36"W x 24"D

- 1-Vertical steel door
- 1-Steel toolbox tray with 500 lb roller bearing sliders and locking latch
- 1-Aluminum bookshelf
- 1-Ceiling light

Driver side #2 – 60"H x 24"W x 24"D 1-Vertical steel door 3-Aluminum shelves 1-Door light

Driver side #3 – 26"H x 42"W x 24"D 2-Vertical steel doors 1-Aluminum shelf 1-Ceiling light

Driver side #4 – 48"H x 30"W x 24"D 1-Vertical steel door 1-Crane reinforcement 1-Aluminum drip tray with drain hose 1-Hook for crane controller and cable (front wall) 1-Door light

Passenger side #1 – 60"H x 30"W x 24"D 1-Vertical steel door 2-Bottle holders with wear pads (front wall) 3-Gear hooks (1 rear wall, 2 back wall) 4-Vertical bar holders with tie down tabs (rear wall) 1-Stainless steel vent (above bottles)

Passenger side #2 – 60"H x 30"W x 24"D 1-Vertical steel door 3-Aluminum shelves 1-Door light

Passenger side #3 – 26"H x 42"W x 24"D

2-Vertical steel doors 1-Aluminum shelf 1-Ceiling light

Passenger side #4 – 48"H x 30"W x 24"D 1-Vertical steel door 3-Aluminum shelves 1-Door light

<u>Cargo bay – 132"D x 48"W x 41"H</u>

- 1-Flip up aluminum roof system with gas cylinders, stainless latching, and two removable aluminum rear panels
- 1-18" tailgate with plastic covered drop chains, adjustable zinc plated latches, hinges with grease nipples and brass inserts, and grip tape

4-Zinc plated rotating d-ring tie downs (6,000 lb capacity each)

Misc. features

- 2-Rear mud flaps
- 2-Aluminum grab handles with rubber grips
- 4-Bosch 8" rooftop swivel halogen floodlights
- 1-7"L smooth steel step bumper with Hippo Liner coating
- 2-Vertical bumper vice receivers