

Commercial generator series PX12000e



Cummins Onan

Performance you rely on.™



Features and benefits

- 10 kW running, 12 kW peak
- 8.2 hour continuous operating time (at rated load)
- Electric start 22 HP, 4-stroke overhead valve engine
- Large 11.4 gallon fuel tank
- 120 V 20 A GFCI protected duplex, 120 V 30 A twist lock, 120/240 V 30 A twist lock, 120/240 V 50 A twist lock, 12 V DC charging
- Volt and hour meter
- Idle control system
- Large muffler w/U.S. Forestry approved spark arrestor
- High performance alternator w/max surge capacity
- 4 wheel kit standard
- 2 year limited warranty
- Meets EPA, CSA standards

Weight, size and sound level

- Weight:** 329 lbs (149.23 kg)
- Size:** Length 33 in (838.2 mm), width 30 in (762 mm), height 34 in (863.6 mm)
- Sound:** Readings at 7 m: 77 dB(A)

* Dimensions include wheel kit

Models and ratings

AC rated output	10kW	DC voltage	12 V
AC max output	12 kW	Engine horsepower	22
AC Voltage	120 V/240 V	Fuel tank capacity	11.4 Gal/43.1 L
AC frequency	60 Hz		
120 V AC rated amperage - Rated/max	83.3 A/100 A		
240 V AC rated amperage - Rated/max	41.7 A/50 A		

Ratings apply to altitudes up to 1000 ft (304.8 m), 85 °F (30 °C). Total power available will decrease 3.5% for each 1000 ft (304.8 m) above 1000 ft and 2.0% for each 10 °F (5.5 °C) increase in ambient temperature above 85 °F (30 °C).

Cummins®, Onan®, the "C" logo and Performance you rely on.™ are servicemarks, trademarks and/or registered trademarks of Cummins Inc. Specifications subject to change without notice. ©2008 Cummins Power Generation. All Rights Reserved.
A-1513a (9/08) (formerly F-1674)