

# Commercial generator series PX6100 & PX6100e



## Cummins Onan

Performance you rely on.™



### Features and benefits

- 4800 watts running, 5800 watts peak
- 7 hour continuous operating time (at rated load)
- Manual start (\*optional electric start)
- 11 HP, 4-stroke overhead valve engine
- Large 5.7 gallon fuel tank
- 120 V 20 A GFCI protected duplex, 120 V 30 A twist lock, 120/240 V 20 A twist-lock receptacles, 12 V DC charging
- Volt meter
- Idle control system
- Full power switch
- Automatic low oil shutdown
- 2 year limited warranty
- Meets EPA, CSA standards

### Weight, size and sound level

- Weight:** PX6100 - 172 lb (78 kg)  
PX6100e - 180 lb (81.6 kg)
- Size:** Length 27 in (685.8 mm), width 19 in (482.6 mm), height 25 in (635 mm)
- Sound:** Readings at 7 m: 75 dB(A)

### Models and ratings

<b>AC rated output</b>	4.8 kW/4800 W	<b>DC voltage</b>	12 V
<b>AC max output</b>	5.8 kW/5800 W	<b>Engine horsepower</b>	11
<b>AC Voltage</b>	120 V/240 V	<b>Fuel tank capacity</b>	5.7 Gal/21.6 L
<b>AC frequency</b>	60 Hz		
<b>120 V AC rated amperage</b> - Rated/max	40 A/48.3 A		
<b>240 V AC rated amperage</b> - Rated/max	20 A/24.2 A		

Ratings apply to altitudes up to 1000 ft (304.8 m), 85 °F (30 °C). Total power available will decrease 3.5% for each 1000 ft (304.8 m) above 1000 ft and 2.0% for each 10 °F (5.5 °C) increase in ambient temperature above 85 °F (30 °C).